



From Tyco Security Products



DSC-D114-28

IR Mini Dome Camera

The DSC-D114-28 is a IR Mini Dome Camera with a rich feature set that makes it ideal for applications that require high definition images and versatile performance even in challenging light conditions.

The DSC-D114-28 incorporates a 2 Megapixel High Resolution CMOS sensor and comes with a 2.8mm F2.0 Fixed Lens. It comes with an IR of upto 30 meters range.

The DSC-D114-28 comes with ONVIF support and has a IP 66 housing.

Features That Make a Difference

2 Megapixel / Dual Codec & Streaming / Powerful IR / 3D DNR

- 2 Megapixel 1/3" Progressive Scan CMOS Image Sensor
- H.264/MJPEG Dual Codec & Streaming
- Fixed Lens 2.8mm F2.0
- Video Resolution 1920 × 1080
- Noise Reduction 3D DNR
- IR Range upto 30 meters
- IP 66 Housing
- Power over Ethernet PoE (802.3af)
- ICR IR cut filter with auto switch
- ONVIF Supported

IR Mini Dome Camera

Specification

DSC-D114-28

Camera

Image Sensor	1/3" Progressive Scan CMOS
Scanning Frequency (H)	1100
Scanning Frequency (V)	1250
Sync System	Internal sync
Video Resolution	1920 × 1080
Minimum Illumination	0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR
Number of Effective Pixels	2MP
Electronic Shutter Speed	1/3 s to 1/100,000 s
S/N Ratio	75db
AGC Compensation	Yes
Exposure Control	Manual/Auto
White Balance Mode	Auto/Fluorescent lamp/Incandescent lamp/Warm light lamp/Natural light
Lens	2.8mm @ f2.0
ICR	IR cut filter with auto switch
Noise Reduction	3D DNR
Mirror	Yes

Image

Codec Image Size (H x V)	1920 x 1080
Video Compression Format	H.264/ MJPEG
Scanning System	Progressive Scan
Codec Streaming	Dual stream
Maximum Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720)60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)

Scene Control

Motion Detection Control	Yes
Privacy Mask Control	Yes

Network

Support Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP, RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP, 802.1X,QoS,IPv6,Bonjour
Frame Rate & Bandwidth Control	Yes
Device Management	32 Kbps – 8 Mbps
Alarm Management	Yes
	Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Number of Client	6
Onvif	Supported
Dynamic Domain Name	DynDns, NO-IP
Security	HTTPS, SSL, password protection, watermark, IP address filtering
Installation & Maintenance	Inclined ceiling mount, wall mount, pendant mount, vertical pole mount, corner mount
System Hardware	ARM

Interface

Ethernet	1 RJ45 10M/100M Ethernet interface
Power over Ethernet	PoE (802.3af)

General

Weight	500g (1.1 lbs)
Dimensions	Φ111 × 82 mm (4.4" × 3.2")
Power Requirements	12 V DC ± 10% , PoE (802.3af)
Power Consumption	Max. 5 W (Max. 7 W as IR cut filter on)
Working Temperature	-30 °C – 60 °C (-22 °F – 140 °F)
Operating Humidity	Humidity 95% or less (non-condensing)
Standard	IP66
	IEC60068-2-75Eh, 20J; EN50102, upto IK10
IR Range	Upto 30 meters

IR Mini Dome Camera

Product specifications and availability subject to change without notice. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.
©2014 Tyco Security Products. 2014-12, Rev 03

Actual products may vary from photos. Not all products include all features. Availability varies by region. Contact your sales representative.

Tyco Security Products
C-602, RMZ Centennial, Kundalahalli Main Road,
Bangalore 560 048, India
Mobile: +91 97396 08889, Tel: + 91 80 40527000
Email :info-tspindia@tycointl.com