

StandardIP Indoor Mini-Dome Camera



Features That Make a Difference:

- 2 megapixels resolution for true HD quality images
- 2.8 12 mm varifocal lens
- True Day/Night (TDN) functionality for true color image
- IR illuminators for clear images in low light conditions
- Wide Dynamic Range
- 3D noise reduction for sharper images and lower bandwidth use in low light
- ONVIF-compliant

The Illustra Standard Indoor Mini-Dome Camera provides 2MP full HD resolution for high quality images. Whether in bright sun, near darkness or blackout conditions, you can clearly see important details, such as merchandise labels, and faces. H.264 video compression provides excellent image clarity and efficient bandwidth and video storage for a cost-effective video solution.

With a small, aesthetically pleasing design, the Illustra Standard Indoor Mini-Dome is ideal for indoors applications offering an effective solution for retail stores, K-12 schools, small bank branches and small to medium size offices with a tight budget

and a variety of surveillance needs. The sensitivity of the sensor and processor combination is enabled through the latest technology, such as True Day/Night. In low light, this camera delivers clear video surveillance. The integrated 2.8 – 12mm varifocal lens delivers an excellent field of view over longer distances providing the video resolution needed for most installations. The Illustra Standard Indoor Mini-Dome comes complete with built-in IR illuminators for clear video images in extreme low light or zero illumination conditions providing crisp, clear video quality both day and night.





Specifications

Operational

Video Compression H.264/MJPEG Day/Night Mechanical ICR Minimum Illumination OLux/F1.4(IR ON)

IR Illumination 10-20M (24xØ5 ÍR Leds) Electronic Shutter Auto/Manual (1/25~1/10000)

HD1080P 1-25/30fps

Sub-stream: CIF/QCIF/D1/Q720P/QVGA/VGA

1-25/30fps

Digital Noise Reduction 3D

Wide Dynamic Range Digital WDR

Motion Detection 4 Zones, Multi-Level Sensitivity

Privacy Zones 4 Zones

Snapshoot......Support JPEG format

Password Protection Support

Character Display Support Channel/ Date

ONVIF Yes

Network

Ethernet RJ45 10M/100M adaptive

Support Protocol.......TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS,

NTP, PPPOE, UPNP, SMTP

Video Output 1.0 Vp-p, 75 ohm, composite,

BNC output

Configuration Management

Web Browsing

Requirements Internet Explorer 9.0 or above

Electrical

Power 12V DC, PoE

Power Consumption < 8W


Physical

Dimension Ø127.7 (W) x 100.2 (H) mm

Regulatory

Emissions FCC Part 15 CE: EN55022 Immunity CE: EN50130-4

Mounts & Accessories



Ordering Information

Model	Description					
ISL02D1ACWIY	Illustra STD Indoor Mini-Dome, WDR, TDN, IR, Varifocal 2.8-12mm, 2MP					
J59	Illustra STD ISL02D1ACWIY Indoor Mini-Dome, Wall Mount					

ILLUSTRA CAMERA MODEL KEY													
ILLUSTRA	SERIES	MODEL	RESOLUTION	FORM FACTOR		ENVIRONMENT HOUSING	BUBBLE	COLOR	DAY/NIGHT/IR	WDR	OTHER		
1	E = Essentials	L = Lite	01 = 1MP	B = Bullet	N = None	N = None	N = None	B = Black	C = Color Only	N = No	A = Hardware Update		
	F = Flex	P = Plus	02 = 2MP	C = Compact Dome	F = Fixed	A = Indoor NonVandal	C = Clear	G = Gray	I = TDN w/IR	T = Multi- Exposure (>60 Frames)			
	P = Pro	S = Standard	03 = 3MP	D = Dome	0 = 1.8 - 3mm	B = Outdoor NonVandal	S = Smoked	S = Silver	S = Soft Day/Night	Y = Yes			
	Q = Edge		05 = 5MP	F = Fisheye	1 = 2.8 - 12mm	I = Indoor Vandal		W = White	T = TDN				
	S = Standard			M = Mini-Bullet	2 = 3 - 9mm	O = Outdoor Vandal							
				P = PTZ	3 = 9 - 22mm								
				W = Wireless Cube	4 = 9 - 40 mm								
				X = Box	5 = 20x								
					6 = 30x								

Related Products



VideoEdge



exacqVision



victor

Approvals

www.tycosp-apac.com

Tyco and the product names listed above are marks and/or registered marks. Unauthorized use is strictly prohibited.

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

Tyco Security Products Asia Pacific Asia Pacific Headquarter Shanghai Tel: +86 400 6858 226

Australia Tel: +61 2 8718 2000

Hong Kong Tel: +852 2753 3015

Singapore Tel: +65 6771 3533

India Tel: +91 80 4052 7000

www.tycosp-apac.com Email: tycosp-apac@tycoint.com