

Standard

3MP Box Network Camera

Features That Make a Difference:

- 3 Megapixel 1 /3" CMOS Sensor in High Resolution
- H.264/MJPEG Dual Codec and Streaming Simultaneously
- Auto-IRIS
- 2048x1536@22fps / 1080P (1920x1080@30fps)
- Digital I/O for External Sensor and Alarm
- Mechanical ICR
- Digital Powerful WDR
- 3D Noise Reduction
- 2 Way Audio Supported
- Intelligent Video Analytics
- 3GPP Supported
- PoE Power Over Ethernet IEEE802.3af
- Micro SD Card Supported (SDHC up to 32GB)
- ONVIF-Compatible



The Illustra Standard 3MP Box Network Camera is a high performance camera with a rich feature set that makes it perfect for applications requiring high definition images. For performance in extremely low light conditions this camera is unbeatable.


This camera by American Dynamics incorporates a 3 Megapixel high resolution CMOS sensor and comes with the additional benefits of triple streaming and multicasting. The advanced 3-D noise reduction feature delivers clear, high quality images.



Specifications

Camera	
Sensor	3 Mega Pixel 1/3' CMOS Sensor
Scan Method	Progressive
Lens	C-Mount / CS-Mount
Number of Effective Pixel (HxV)	2048x1536
Minimum Illumination	Day Mode: 0.1 Lux Night Mode (B/W): 0.01 Lux
SNR(max)	55db
White Balance	Auto
Gain Control	High/ Middle/ Low, 3 step selection
Day and Night	ICR (Auto control by photo sensor, Manual control by CGI) IR-Cut Filter Removable
DNR	Yes
Flicker Control	3 steps selection (Off, 50Hz, 60Hz)
Electronic Shutter	Auto, Slow shutter 5 steps selection (Off, 2x, 4x, 8x, 16x)
BLC/D-WDR	On / Off
Intelligent Video	
Video Compression	H.264 BP, MJPEG dual codec, dual streaming, multiple profiles
Video Framerate	Dual Streaming
Resolution	H.264: 5MP(2560x1920@15fps) / 1080P(1920x1080@30fps) / 720P(1280x720@30fps) MJPEG: 5MP(2560x1920@5fps) / 1080P(1920x1080@30fps) / 720P(1280x720@30fps)
Bitrate control	Both CBR and VBR, 32 kbps to 8 mbps
Multi-streams	1080P@30fps+720P@30fps
Digital Zoom (PC side)	Yes, 1/2X, 1X, 2X, 4X
Image Rotation	Mirror, Flip, Rotate 180°
Audio	
2 Way Audio	Yes
Compression	AMR, G.711 @ 64kbps, G.726@ 32kbps/ Configure bitrate
Network	
Supported Protocols	RTSP/RTP/UDP, RTSP/RTP/TCP, RTSP/RTP/HTTP tunneling, LAN Multicast, Multipart-JPEG, 1Pv4, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP, FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP, Telnet, IP, IGMP V2/V3, ICMP, SNMP
3GPP Mobile Surveillance	Yes
Storage	
External	1x Micro SD card
I/O and Connectors	
LAN	1xRJ45 Ethernet connector with LED
Alarm I/O	1xAlarm-in (2pin), 1xAlarm-out (3pin)
Audio	1xAudio Microphone-in (3.5mm jack), 1xAudio Line-out (3.5mm jack)
Software Compatibility	
Browsers	Internet Explorer 6.0 or above
Factory Default	
	Button
Power	
Power Consumption	DC 12V, DC 12V/ POE, 3.6W
Dimension	
	162.5mm(W) x 59mm(H) x 65mm(D)
Weight	
	395g
Operating Environment	
Operating Temperature	-10°C ~ +50°C
Storage Temperature	-20°C ~ +70°C
Humidity	0% ~ 95% non-condensing
Certification	
	CE, FCC Class A, RoHS, EMC

Dimension Diagram



Ordering Information

Illustra Standard Model No.	Description
ISS03XNNNGSY	3 MP Box camera

Related Products



VideoEdge



victor



exacqVision

Approvals



www.tycosp-apac.com

© 2015 Tyco Security Products. All Rights Reserved. 08/2015/R01

Tyco and the product names listed above are marks and/or registered marks. Unauthorized use is strictly prohibited. Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

Tyco Security Products Asia Pacific
Asia Pacific Headquarter Shanghai
Tel: +86 400 6858 226

Australia
Tel: +61 2 8718 2000

Hong Kong
Tel: +852 2753 3015

Singapore
Tel: +65 6771 3533

India
Tel: +91 80 4052 7000

www.tycosp-apac.com
Email: tycosp-apac@tycoint.com