

# Standard

## 2MP IR Mini Bullet Cameras



### Features That Make a Difference:

- 2 Megapixel 1/2.8" Progressive Scan CMOS
- 4mm & 6mm Lens options
- 1920 × 1080 Full HD Video
- H.264/MJPEG Dual Codec & Streaming
- Up to 25 fps frame rate
- Digital WDR
- 3D DNR
- IR cut filter with auto switch
- Up to 30m IR range
- ONVIF-Conformant
- Support 128GB on-board storage
- IP66 Housing
- DC12V / PoE

The Illustra Standard mini bullet Camera by American Dynamics captures good quality images with a rich feature set that makes it ideal for applications that require high definition images and versatile performance even in challenging light conditions.

### Exceptional Image Quality

With a Full HD 1920 × 1080 resolution @25fps the camera produces exceptional Image quality and supports H.264/MJPEG video compression.

This mini dome camera has standard in-built support to 128GB Micro SD/SDHC/SDXC card storage.

The ISL02MFONWIN and ISL02MFONSIN deliver high performance and offer great value. The cameras incorporate a 2 Megapixel, high resolution 1/2.8" progressive scan CMOS sensor.

The ISL02MFONWIN comes with a 4mm F2.0 Fixed Lens whereas the ISL02MFONSIN has a 6mm F2.0 Fixed Lens.

For superior night time rendering of video images, both cameras perform effectively over a greater IR coverage range of up to 30 meters. The cameras come with ONVIF support and have IP 66 housing




## Specifications

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR 0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	4mm@ F2.0, Angle of view: 85° (6mm optional)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Compression Standard	
Video Compression	H.264/ MJPEG
Video Bit Rate	32 Kbps – 8 Mbps
Dual Stream	Supported
Image	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable
Backlight compensation	Supported
ROI	Supported

Network	
Alarm Trigger	Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface
On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Reset Button	Yes
General	
Regulatory	CE, FCC
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10%, PoE (802.3af)
Power Consumption	5W MAX (Max. 7 W with IR cut filter on)
Ingress Protection level	IP66
IR Range	Up to 30 meters
Dimensions	70×157×62mm (2.8" × 6.1" × 2.4")
Weight	500g (1.1 lbs)

## Dimensions



## Ordering Information

Model Number	Description
ISL02MFONWIN	2MP IR Mini Bullet with 4mm Fix lens
ISL02MFONSIN	2MP IR Mini Bullet with 6mm Fix lens

## Related Products



Illustra  
Standard NVR



Holis  
Standard NVR



Mobile App

## Approvals



[www.tycosecurityproducts.in](http://www.tycosecurityproducts.in)