



Release Notes

Illustra Standard IP Camera ISS08DN1CWIT ISS08BN1NWIT

Applicable Software	Product Data
Firmware version: V3.1.0.180503	Visit the Network Video Recorders section of our web site – http://www.tycosecurityproducts.in – to download datasheets and other documentation in PDF format.

May. 2018

Note

In case of discrepancy, the information in this document supersedes the information in any document referenced herein.

Table of Contents

Table of Contents 2

What’s new in This Release 3

What’s New 3

Key Feature 3

Limitation 3

What's new in This Release

What's New

ISS08DN1CWIT & ISS08BN1NWIT Firmware V3.1.0.180503

The camera ISS08DN1CWIT & ISS08BN1NWIT are 8M WDR vari-focal network IP camera, able to capture high quality colored images up to 3840 × 2160 and 120dB WDR.

Key Feature

- 1/2.5" Progressive Scan CMOS
- 3840 × 2160 resolution
- H.265, H.265+
- 120dB WDR
- IP67, IK10
- BLC/3D DNR/ROI
- Smart encoding: Support low bit rate, low latency
- 4 behavior analyses and face detection
- Multiple network protocols, including TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS,SNMP, NTP, PPPoE, UPnP, SMTP
- AD_connected and illustraConnect discovery tool
- ONVIF V2.4 Profile S , Profile G
- Integration with VideoEdge (v5.2 or above) with API (IllustraStandardIN_Series-5.2.100.2004010)
- Integration with exacqVision (v9.2 or above) via ONVIF

Limitation

1. There will be little jitter at moving object with higher speed on exacqVision (v8.8 and v9.1), it will be improved when exacqVision add smooth stream policy on ONVIF plugin.
2. It cannot be added camera to VE via https mode (VE v5.2)