

# Standard

## 2MP Varifocal Network Bullet Camera

### Features That Make a Difference:

- 1/2.8" Progressive Scan CMOS
- 1920 x 1080@30fps
- 2.8 to 12 mm Motorized vari-focal lens
- Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR
- H.265+, H.265, H.264+, H.264
- Three streams
- 120dB WDR
- 2 behavior analyses, and face detection



The new Illustra Standard 2MP Bullet Camera by American Dynamics comes with a varifocal lens and has several intelligent functions in-built for high-quality video surveillance. Additionally, this Full HD Camera comes with a rich feature-set that includes 120dB WDR, PoE, and 3D DNR to meet a wide variety of Video Surveillance applications.

### Superior IR Performance

An in-built IR covering up to 50 meters range provides high quality colored images in low light conditions.

### Camera Function

The resolution of the Camera is up to 1920 x 1080 @up to 30FPS. It supports H.265+/ MJPEG video compression and Baseline/ Main/High Profile encoding complexity.

The camera supports 120 dB WDR and Backlight Compensation.

### Ideal for Outdoor Applications

The Camera supports the ONVIF (profile S & profile G) protocols, Video Stream recording and live view at different resolutions.

### Ideal for Outdoor Applications

Ingress Protection is at the IP67 level with anti-thunder, anti-surge, anti-static protection that makes this camera ideal for Outdoor Video Surveillance applications.

### ONVIF Support

The Camera supports the ONVIF (profile S & profile G) protocol, Video Stream Recording, live view at different resolutions and bitrate configuration options.



## Specifications


| Camera                  |  |
|-------------------------|--|
| Image Sensor            | 1/2.8" Progressive Scan CMOS   |
| Min. Illumination       | Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR  |
| Shutter Speed           | 1/3 s to 1/100,000 s   |
| Slow Shutter            | Yes  |
| Day & Night             | IR Cut Filter  |
| Digital Noise Reduction | 3D DNR   |
| WDR                     | 120dB  |
| 3-Axis Adjustment       | Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°   |
| Lens                    |  |
| Focal length            | 2.8 to 12 mm Motorized Vari-Focal lens   |
| Aperture                | F1.6   |
| Focus                   | Auto   |
| FOV                     | horizontal FOV: 110° to 31°<br>vertical FOV: 58° to 18°<br>diagonal FOV: 136° to 36°                                       |
| IR                      |  |
| IR Range                | Up to 50 m   |
| Wavelength              | 850nm  |
| Compression Standard    |  |
| Video Compression       | Main stream: H.265/H.264<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264                                     |
| H.264 Type              | Main Profile/High Profile  |
| H.264+                  | Main stream supports   |
| H.265 Type              | Main Profile   |
| H.265+                  | Main stream supports   |
| Video Bit Rate          | 256 Kbps to 16 Mbps  |
| Smart Feature-set       |  |
| Behavior Analysis       | Line crossing detection, intrusion detection   |
| Face Detection          | Yes  |
| Region of Interest      | 1 fixed region for main stream and sub-stream  |
| Image                   |  |
| Max. Resolution         | 1920 × 1080  |
| Main Stream             | 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)<br>60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)                     |
| Sub-Stream              | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)                             |
| Third Stream            | 50Hz: 25fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 240) |
| Image Enhancement       | BLC/3D DNR/HLC   |
| Image Setting           | Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser                      |
| Day/Night Switch        | Day/Night/Auto/Schedule/Triggered by alarm in (-S)   |

| Network                       |   |
|-------------------------------|---|
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G) ; local storage  |
| Alarm Trigger                 | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error                  |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| General Function              | One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter    |
| API                           | ONVIF (PROFILE S, PROFILE G),   |
| Simultaneous Live View        | Up to 6 channels  |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User  |
| Web Browser Interface         | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+  |
| Audio (-S)                    | 1 input (line in/mic.in), 1 output (line out), mono sound, terminal block   |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port   |
| Alarm (-S)                    | 1 input, 1 output (max. 12 VDC, 30 mA), terminal block  |
| Video Output                  | 1Vp-p composite output(75Ω/BNC) (For adjustment only)   |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB  |
| SVC                           | H.264 and H.265 encoding  |
| Reset Button                  | Yes   |
| Audio (-S)                    |   |
| Environment Noise Filtering   | Yes   |
| Audio Sampling Rate           | 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz   |
| Audio Compression             | G.711/G.722.1/G.726/MP2L2/PCM   |
| Audio Bit Rate                | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)   |
| General                       |   |
| Operating Conditions          | -30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)   |
| Power Supply                  | 12 VDC ± 25%, terminal block PoE (802.3at, class 4)   |
| Power Consumption and Current | 12 VDC, 1.2A, max. 14.5W PoE (802.3at, 42.5V to 57V), 0.43A to 0.3A, max. 18W   |
| Protection Level              | IP67, IK10  |
| Material                      | Metal   |
| Dimensions                    | Ø 105.1 × 297.5 mm (Ø 4.1" × 11.7")   |
| Weight                        | Camera: Approx. 1285 g (2.8 lb.) With Package: Approx. 1964 g (4.3 lb.)   |

## Ordering Information

| Model Number | Description                              |
|--------------|--|
| ISL02M1BNWIT | 2 MP IR Bullet with Varifocal lens, TWDR |

## Dimensions



## Related Products



VideoEdge



victor



exacqVision

## Approvals



[www.tycosecurityproducts.in](http://www.tycosecurityproducts.in)